



DAIHATSU
APPLAUSE



APPLAUSE









Specifications

Item	Grade	Li	Xi
Overall length	mm	4350	
Overall width	mm	1660	
Overall height	mm	1385	
Wheelbase	mm	2470	
Track	Front	mm	1425
	Rear	mm	1415
Minimum road clearance	mm	140	
Kerb weight	5M/T	kg	975
	4A/T	kg	1015
Gross vehicle weight	5M/T	kg	1470
	4A/T	kg	1515
Seating capacity		5	
Min. turning radius (tyre)	m	4.8	
Engine type		HD-E, petrol, transverse water-cooled, in-line 4-cylinder, 4-cycle, 16-valve, SOHC	
Total displacement	cc	1590	
Bore x stroke	mm	76.0 x 87.6	
Max. output (EEC)		73 kW/6000 rpm	
Max. torque (EEC)		138 N-m/3600 rpm	
Compression ratio		10.5	
Fuel system		Electronic fuel injection	
Fuel tank capacity	litres	50	
Clutch (manual transmission)		Dry single plate with diaphragm spring and mechanical actuation	
Transmission type	5M/T	Forward 5-speed manual, all-synchromesh	
	4A/T	Forward 4-speed full automatic	
Transmission gear ratio	5M/T	1st-3.090, 2nd-1.750, 3rd-1.250, 4th-0.916, 5th-0.750, Rev-3.142	
	4A/T	1st-3.643, 2nd-2.008, 3rd-1.296, 4th-0.892, Rev-2.977	
Final reduction gear ratio	5M/T	4.266	
	4A/T	2.821	
Steering type		Rack and pinion	
Main brake	Front	Ventilated disc type with booster	
	Rear	Drum type, leading and trailing	
Parking brake		Mechanical type, 2-rear wheel lock	
Suspension	Front	MacPherson strut	
	Rear	MacPherson strut, dual link	
Tyres (standard)		175/70R13	

Note: Daihatsu reserves the right to make changes at any time, without notice, in prices, colours, materials, equipment, specifications and models, and also to discontinue models. This publication is for international usage, and some specifications and illustrations do not necessarily conform with the models sold in your market.



DAIHATSU MOTOR CO., LTD.

1-1, Daihatsu-cho, Ikeda, Osaka 563, JAPAN